



2013 Workshop on Accelerated Stress Testing and Reliability



Accelerated Testing of Locking Electrical Connectors

Adam Bahret



2013 Workshop on Accelerated Stress Testing and Reliability



Introduction

- Selection of electrical connectors for a harsh outdoor environment requires extensive testing to validate robustness.
- Each application has it's own special set of requirements which make a standard selection unlikely even for derivative products.
- Stresses such as high vibration, repetitive impact, and dirt intrusion are factors



2013 Workshop on Accelerated Stress Testing and Reliability



Application

- The electrical connectors to be selected were for digital communication in an all weather, half ton, hydraulic driven robot with an internal combustion power source
- Sources of stress for the connectors were
 - Engine vibration
 - Foot impact with ground
 - Hydraulic rhythm
 - Frequent Impact with surrounding obstacles



2013 Workshop on Accelerated Stress Testing and Reliability



The Challenge

- Digital communication connections that were exposed to the elements and in a chassis with continuous vibration and impact would likely have a high failure rate if not properly validated and optimized.
- This was confirmed with field testing that saw frequent broken or intermittent communication issues
- The gating factor for the development program was being able to do testing quickly so design iterations could maintain with the program pace.





Types of Connectors

- There were two types of all weather connectors being considered
- Latch-lock
 - Latch-lock have a latching prong that hold the connector in place
- Cam-lock
 - Cam-lock connectors have a twisting collar that passes an over-center feature during rotation (cam) and locks the connector


Snap Fit Connector

- Features of a common latch-lock weather proof connector



Cam Lock Connector

- Features of a common cam-lock weather proof connector





2013 Workshop on Accelerated Stress Testing and Reliability



Design Trade Offs

- Both Design could be made weather proof with sealing o-rings or gaskets
 - The latch lock were light and easy to insert
 - The Cam-lock can handle higher loads but were heavy and create larger harnesses
- The initial selected design was a latch-lock type of connector with a sealing boot
- Instances of intermittent and failed connections were reported in field testing with the robot with this design



2013 Workshop on Accelerated Stress Testing and Reliability



IEEE COMPONENTS, PACKAGING AND
MANUFACTURING TECHNOLOGY SOCIETY



Reliability
Division
The Global Voice of Quality™

The Testing Need

- A test method that could be done quickly and in a lab environment was needed to assist with selecting a weather proof design robust enough to handle the impact and vibration environment of this application



2013 Workshop on Accelerated Stress Testing and Reliability



Impact Testing

- The initial test was based on the premise that a single or short sequence of impacts could be used to correlate connection failure to long term repetitive vibration stress
- Using 50g's as an increment the test was done to the candidate connectors
- It wasn't until 300g's that a failure was observed in the standard latch (weakest) connector
- But the impact tester was taken to it's limit before any other failures could be observed

1,500 g Impact

- The impact tester was able to deliver 1,500 g's of force

This is what 1,500 g's looks like!!
Click Image to Play Video



- All other locking connectors were able to withstand this impact, so test could not be used as comparator for all candidate connectors

Vibration

- Using a HALT chamber, six axis broadband vibration was applied to the “latch-style” and “cam-style” connectors
- Vibration was driven up to 90 Grms with no observed failures



Backside of Baseplate

Connector

baseplate

breadboard

HALT Table





The Challenge of Failure

- It was becoming apparent that creating enough stress using standard lab techniques to make a strength comparison between locking connectors was difficult
- The effects of long term vibration and repetitive impact in the robot application was difficult to duplicate in a shortened controlled time frame.



2013 Workshop on Accelerated Stress Testing and Reliability



The Solution

- An additional stress amplifier was needed to create resolution between the robustness of the different connector designs
- This “accelerator” had to be adjustable in orders of magnitude so comparative performance could be discovered and then focused on
- The solution was creating an adjustable cantilevered load on the connectors to be used during HALT vibration or impact testing




2013 Workshop on Accelerated Stress Testing and Reliability



The Solution

- The variable cantilevered load was created by clamping threaded rods to the connectors
- Weights of varying size could then be added to the rods at varying distance to create a controlled amplifier
- If a group of failures are separated by a large margin the stress can be raised by an order of magnitude without breaking down the setup

Cantilever Load Setup





ReliabilitySociety

2013 Workshop on Accelerated Stress Testing and Reliability




IEEE COMPONENTS, PACKAGING AND
MANUFACTURING TECHNOLOGY SOCIETY



Reliability
Division
The Global Voice of Quality™

12 oz of weight (3/4 lb)





ReliabilitySociety

2013 Workshop on Accelerated Stress Testing and Reliability




IEEE COMPONENTS, PACKAGING AND
MANUFACTURING TECHNOLOGY SOCIETY



Reliability
Division
The Global Voice of Quality™

22 oz of weight (1.5lb)





2013 Workshop on Accelerated Stress Testing and Reliability



Results

- The accelerated test development initiative resulted in the ability to apply enough cumulative stress to replicate the failures observed in the field on any connector configuration